

# CMA 5000

## Optical Spectrum Analysis Application



The OSA module maintains industry leading accuracy performance over the entire temperature and spectral range.



### Ideal Solution For Any Test Scenario

As a part of the CMA 5000 platform, the OSA application is just one other way to accelerate the deployment of services while reducing the cost of measurement. With test and measurement options ranging from OTDR, connector inspection and dispersion to optical spectral analysis, bit error rate, SONET/SDH analysis and Gigabit Ethernet, the CMA 5000 is the ideal single solution for all your testing needs.

Today's competitive environment demands that networks offer exceptional performance and reliability with minimal down time. When characterizing and documenting such stringent performance levels, the CMA 5000 Optical Spectrum Analysis (OSA) application is the ideal single solution for facilitating accurate and efficient channel management, power balancing and tuning throughout the network. The OSA application lowers DWDM installation and maintenance costs by providing industry leading spectral analysis of system critical parameters.

Operating from 1450-1650 nm (S-, C- and L-band), the OSA module for the CMA 5000 maintains industry leading accuracy. In addition, 30 dB of OSNR at 25 GHz channel spacing is perfect for testing high capacity DWDM systems.

Increased revenue through accurate channel characterization:

- 30 dB of OSNR at 25 GHz channel spacing


- +20 pm wavelength accuracy
- +0.3 dB power accuracy

Added value through performance:

- **Exclusive Channel Select option allows user to drop a wavelength for additional analysis**
- **Wide spectral range for characterization of the S-, C-, and L-bands with a single unit**
- **High resolution, double pass Diffraction Grating technology**

Reduced cost of measurement:

- **Easy-to-use - one button complete spectral characterization**
- **User-defined configurations for custom DWDM testing**
- **Reduced test time through targeted applications**



OSA Specifications	
<b>Technology</b>	Diffraction Grating
<b>Wavelength Range</b>	1450 - 1650 nm
<b>Wavelength Accuracy<sup>1</sup></b>	±40 pm (±20 pm typical)
<b>Wavelength Repeatability<sup>1,2</sup></b>	±5 pm
<b>Resolution Bandwidth<sup>3,4</sup></b>	85 pm FWHM (typical)
<b>Channel Spacing (minimum)</b>	25 GHz
<b>Power Range<sup>4,5</sup></b>	+15 to -65 dBm
<b>Power Accuracy<sup>1</sup></b>	±0.3 dB
<b>Power Linearity<sup>2</sup></b>	±0.1 dB
<b>Power Repeatability<sup>1,4,6</sup></b>	±0.1 dB
<b>Stability</b>	±0.2 dB per hour
<b>Optical Signal to Noise Ratio<sup>4,7</sup></b>	>40 dB @ ±100 GHz >35 dB @ ±50 GHz >30 dB @ ±25 GHz
<b>Channel Table</b>	256 simultaneous
<b>Sweep Time</b>	4 seconds typical over full spectrum
<b>Polarization Dependence Loss<sup>1,2,8</sup></b>	<±0.05 dB
<b>Optical Return Loss</b>	>35 dB
<b>Internal Reference</b>	Yes
<b>Channel Drop Feature</b>	5 dB maximum loss (Optional)
<b>Operating Temperature</b>	0° to 40° C (32° to 104° F)
<b>Storage Temperature Range</b>	-20° to 70° C (68° to 162° F)
<b>Humidity</b>	95% RH non-condensing
<b>Connector Types</b>	UFC, USC, AFC, ASC

#### Notes

<sup>1</sup> Signal from +5 to -30 dBm

<sup>2</sup> At 1550 nm

<sup>3</sup> Full width at half maximum (FWHM) value

<sup>4</sup> 1500 nm to 1620 nm

<sup>5</sup> Typical noise filter -70 dBm; maximum total power +30 dBm

<sup>6</sup> Over 15 minutes at 23° ± 2° C

<sup>7</sup> For signal above 0 dBm (noise computed in a 0.1 nm equivalent bandwidth)

<sup>8</sup> Add ± 0.05 dB for the filter option

Specifications are subject to change without notice



#### NetTest A/S

Kirkebjerg Allé 90  
DK-2605 Brøndby  
Denmark  
Tel: +45 72 11 23 00  
Fax: +45 72 11 23 50  
E-mail: nordic@nettest.com

#### NetTest Sales Offices

Brazil	+55 11 5505 6688	Italy	+39 06 43 36 24 00
China	+86 10 6467 9888	Singapore	+65 6220 9575
Denmark	+45 72 11 22 00	Spain	+34 91 372 92 27
France	+33 1 49 80 47 48	USA	+1 315 266 5000
Germany	+49 89 99 89 01-0		

NetTest, the pioneer in multi-layer network testing, is a global provider of test and measurement systems, instruments and components for all types of networks and all stages of network development and operation. Our solutions offer leaders in optical, wireless and fixed networking vital insights into network performance, enabling informed business decisions that drive profitability.